## accuc@ld

# **ARS3PV**



34" x 18.5" x 19" (H x W x D)

Performance series Pharma-Vac 3 cu.ft. counter height allrefrigerator for vaccine storage

### **Highlights:**

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

Additional sensor reads interior air temperature for superior temperature control

#### **Product Features:**

Purpose-built design	Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC guidelines
+/-1°C Variation	The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period
Adjustable temperature	Intuitive controls let you adjust the interior temperature between +2 to +8°C
Temperature alarm	Visual and audible alarms alert if the interior temperature rises or falls out of set range
Remote alarm contacts	Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)
Automatic defrost with adjustable cycle defrost	Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup
Access port	Includes a pre-installed 1/2" probe hole in the right interior wall to allow easier connection to user-provided monitoring equipment
Open door alarm	Alarm will sound if the door is left ajar for over 4 minutes (adjustable from 1-99 minutes)
Audible power failure alarm	Battery-powered alarm sounds if the power connection is interrupted



## accuc@ld

### **ARS3PV Specifications:**

Overview		
Height of Cabinet	34.0" (86 cm)	
Width	18.5" (47 cm)	
Width with Door Open	19.0" (48 cm)	
Depth	19.0" (48 cm)	
Depth with Handle	20.75" (53 cm)	
Depth with door at 90°	36.0" (91 cm)	
Capacity	3.0 cu.ft. (85 L)	
Defrost Type	Automatic	
Door	White	
Cabinet	White	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Amps	0.6	
Voltage/Frequency	115 V AC/60 Hz	
Weight	90.0 lbs. (41 kg)	
Shipping Weight	100.0 lbs. (45 kg)	
Estimated Time to Ship	1 to 2 days	
Parts & Labor Warranty	2 Years	
Compressor Warranty	5 Years	
Refrigerator Features		
Door Swing	RHD	
Reversible	Yes	
Reversible Shelf Type	Yes Wire	
Shelf Type	Wire	
Shelf Type Shelf Qty	Wire 4	
Shelf Type Shelf Qty Adjustable Shelves	Wire 4 Yes	
Shelf Type Shelf Qty Adjustable Shelves Thermostat Type	Wire 4 Yes Digital	
Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type	Wire 4 Yes Digital Interior	
Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type	Wire 4 Yes Digital Interior R600a	
Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount	Wire 4 Yes Digital Interior R600a 1.06oz.	
Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light	Wire 4 Yes Digital Interior R600a 1.06oz. Yes	
Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light Temperature Range	Wire 4 Yes Digital Interior R600a 1.06oz. Yes	
Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light Temperature Range Dimensions	Wire  4  Yes  Digital  Interior  R600a  1.06oz.  Yes  2 to 8°C	
Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light Temperature Range Dimensions Interior Height	Wire  4  Yes  Digital Interior  R600a  1.06oz.  Yes  2 to 8°C	
Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Fan Type Refrigerant Type Refrigerant Amount Interior Light Temperature Range Dimensions Interior Height Interior Width	Wire  4  Yes  Digital  Interior  R600a  1.06oz.  Yes  2 to 8°C  28.38" (72 cm)  15.25" (39 cm)	



